

MODEL NDI 450

AUTOMATED ATMOSPHERIC DISTILLATION OF PETROLEUM PRODUCTS



STANDARDS

ASTM D86 - D850 - D1078 - ISO 3405 - IP 123 - IP 195 - GOST B - JIS K2254 - DIN 51751 and related methods.

SCOPE

This test method covers the atmospheric distillation of petroleum products. Natural, motor and aviation gasolines, aviation turbine fuels, special boiling point spirits, naphthas, white spirit, kerosene, gas oils, distillate fuel oils.

NDI 450 is the 5th generation of automated distillation developed by Normalab. Normalab has been designing and manufacturing petroleum testing instruments and glassware since 1963.



« OUR FLEXIBLE SOFTWARE
WILL MEET
YOUR EXPECTATIONS »»

SPECIFICATIONS

- **Temperature measurement range: ambient to 450°C**
- Temperature accuracy: 0.05°C
- **Low voltage heating element (850W)**
- **Automatic positioning of heating element**
- Quick cooling of heater by fan
- Condenser temperature: 0 to 60°C
- Receiver compartment temperature: 0 to 60°C
- Level follower accuracy: 0.1 ml with resolution of 0.05ml
- **Built-in Peltier Cooling System**
- Ready for Biodiesels analysis
- Integrated colour touch screen display (10,4 inch)
- **Windows® based software**
- Preprogrammed with Standard Methods
- User programmable methods
- Automatic Barometric pressure correction
- Automatic Cetane Index calculation (ISO 4264)
- **Equipment ready to use as per ASTM D86 and related methods (Optional kit for ASTM D850, D1078)**
- Additional Test Method : ASTM D189, D524 & D4530
10% Distillation residue with 100ml sample.



Automatic N₂ Fire Extinguisher

SAFETY FEATURES

- Automatic Fire detection
- **Automated Fire extinguisher (N₂ bottle delivered with the unit)**
- Extinguisher push button
- Sample overheating protection at 600°C
- Sensors:
 - Receiver in position
 - Compartment door: closed
 - Drip deflector in position
 - PT 100 probe: in position
 - Coolant liquid: low level detection
 - N₂ minimum pressure required

CONNECTIVITY

- 3 USB ports
- 1 LAN port
- 1 RS232 port
- 1 VGA port

ORDERING INFORMATION

NORMALAB production - Fully automated atmospheric distillation unit

60502

NDI 450 operable through integrated touch screen and Windows® based software. Equipment with built in fire extinguishing system and external N₂ bottle fitted with manometer for pressure control.

Scope of delivery

NDI 450 delivered ready to use for D86 and related standards:

- 125 ml distillation flask (P/N: 24019)
- 100 ml receiver (P/N: 26111)
- 38 mm heating plate (P/N: 60507)
- 50 mm heating plates (P/N: 60508)
- 5 ml residue receiver (P/N: 12609EC)
- Pt 100 probe (P/N: 60510)
- Pt 100 probe centering device
- Dry point Thermocouple (P/N: 60509)
- Bag of Pumice (20g) (P/N: 60514)
- Condenser cleaning cable (P/N: 60513)
- 3 Stoppers: condenser stopper (P/N: 60515) / flask probe stopper D86 (P/N: 40065) / flask probe stopper D86 for dry point application (P/N: 40064)

Site requirements

Power Supply: **AC 230 V, 50/60 Hz - 9A**

Dimensions: (W) 54cm x (D) 45cm x (H) 63cm

Weight: ±70 kg

60503

Same as 60502 except:

Power Supply: **AC 115 V, 50/60 Hz - 9A**

***Optional kit for ASTM D850, D1078 and related methods (P/N: 60517)**

SUMMARY

Temperature range	Ambient to 450°C	Barometric pressure correction	Automatic
Temperature accuracy	0,05°C	Sample overheating protection	Integrated 600°C
Condenser temperature	0 to 60°C	Fire detection	Integrated
Receiver Comp temperature	0 to 60°C	Fire extinguisher	Integrated
Heating element power	Low voltage 850W	Extinguisher push button	Integrated
Heating element positioning	Automatic	N ₂ bottle	Integrated
Cooling system	Peltier integrated	Software	Windows®
Level follower	2 Photoelectric forks	LIMS connection	RS232 / LAN
Level follower accuracy	0,1 ml	LIMS format	XML/ASCII/CSV
Level follower resolution	0,05 ml	Email reporting	Integrated



CONTACT : sales@normalab.com

Normalab FRANCE SAS
ZA Caux Multipôles 1 - 76190 Valliquerville
France
Tel. : +33.232.700.100
Fax : +33.232.704.732

DISTRIBUTED BY